


Precise Verification of Transformers through ReLU-Catalyzed Abstraction Refinement

Hengjie Liu¹ Zhenya Zhang^{1,2} Jianjun Zhao¹

¹Kyushu University ²National Institute of Informatics

Why certify Transformer robustness?


Small, meaning-preserving changes such as paraphrases, synonyms, or typos should not change a model's decision. Verification aims to prove this for a **complete perturbation region**, rather than test a finite sample.



$$\forall X' \in \text{Perturbed}(X), \quad f(X') = f(X).$$

Sound over-approximation scales to realistic models, but loose bounds can produce false alarms and unnecessary “unknown” results.

Self-attention creates a bilinear bottleneck




The first attention MatMul forms a score matrix:

$$S = QK^\top, \quad S_{ij} = \sum_{h=1}^d q_{ih}k_{jh} \implies z = xy.$$

- Both Q and K depend on the perturbed input, so *both* factors in every scalar product are uncertain.
- This bilinear nonlinearity couples tokens and is harder to bound tightly than the usual affine-plus-ReLU layer.


Why linear relaxation matters



- A nonlinear function can be enclosed by sound linear bounds over a known input interval.
- Linear bounds propagate efficiently through later matrix multiplications and additions.
- We want the same scalability for $z = xy$, but with a tighter relaxation than a single fixed plane.

Key observation: one sound plane is not enough

Prior Transformer verification uses one sound upper plane l^{U_1} . The dual plane l^{U_2} is also sound, and **each is tighter in a different region**.



The ideal upper envelope selects the tighter plane pointwise:

$$l^* = \min(l^{U_1}, l^{U_2}).$$

This envelope is more precise, but it is piecewise and cannot be directly propagated by a linear-bound verifier.

Contributions


- A **ReLU-based representation** fuses two complementary sound planes for attention dot products, connecting Transformer verification with mature ReLU-relaxation techniques.
- The existing planar bound and its dual become endpoint instances of one family; every $\alpha \in [0, 1]$ remains formally sound.
- r-BuFFeT** makes a fast interval-guided choice, while **o-BuFFeT** optimizes α for the final certified margin.
- Across **10 Transformer models and 1,400 verification tasks**, the tighter relaxation certifies substantially larger perturbation radii while exposing an explicit precision–runtime trade-off.

ReLU makes the tighter envelope tractable

BuFFeT rewrites the pointwise choice as a familiar ReLU and then applies a sound linear relaxation:

$$l^* = l^{U_1} - \text{ReLU}(l^{U_1} - l^{U_2}),$$

$$l_\alpha^* = (1 - \alpha)l^{U_1} + \alpha l^{U_2}, \quad \alpha \in [0, 1].$$





The bound $\text{ReLU}(t) \geq \alpha t$ converts the nonlinear minimum into a linear blend. The choice of α controls precision while every $\alpha \in [0, 1]$ preserves soundness.

Two strategies serve different verification budgets

Method	How α is chosen	Practical role
r-BuFFeT	Select $\alpha \in \{0, 1\}$ from the ReLU input interval	One-pass refinement with low overhead
o-BuFFeT	Optimize $\alpha \in [0, 1]$ for the final certified margin	Stronger refinement for difficult cases

Both methods reuse mature ReLU-relaxation machinery and remain formally sound; they differ in how much computation is spent tightening the bound.

RQ1: BuFFeT certifies larger perturbations




Each point is a verification task; points above $y = x$ certify a larger maximal radius ϵ than CrownBaF. The separation grows most clearly on deeper models and appears on both SST and Yelp.

1.8×
maximum r-BuFFeT gain
on 6-layer models

3.6×
maximum o-BuFFeT gain
on 6-layer models

RQ2: Optimization can rescue inconclusive cases



- The blue curve is the certified margin lower bound $M(\alpha)$.
- The dashed zero line is the safety threshold.
- As α is optimized, crossing $M(\alpha) = 0$ turns an inconclusive result into a formal certificate.

RQ3: Precision comes with a clear runtime trade-off

1.1–1.7×
r-BuFFeT runtime
relative to CrownBaF

33.5–96.9×
o-BuFFeT runtime
relative to CrownBaF

r-BuFFeT remains in the same order of magnitude as the baseline and is the practical default. o-BuFFeT pays for repeated optimization when the tighter certificate justifies the additional cost.

Takeaway

ReLU-based bound fusion bridges classic neural-network verification and Transformer attention. Use **r-BuFFeT** for low-cost improvement, then **o-BuFFeT** when eliminating false alarms justifies additional optimization.